

DC Inverter MMA Welding Machine

Features

- ◆ With good protection of under voltage, over voltage and over current, it makes the machine safe and reliable.
- ◆ Self-adaptive power switch, wide range from 360 Volt to 480 Volt for three phase.
- ◆ CC feature, with stable arc.
- ◆ Original imported New Generation IGBT, with high stability.
- ◆ With advanced high efficiency inverter technique 30KHz, high frequency, energy saving and environmental protection.
- ◆ Effectively solved the problem of unstable power supply by using generator during outdoor work.
- ◆ VRD on/off switch YADRIKA-400



Accessories



Main Technical Parameters :

	YUVA-200NW
Input voltage (V)	AC220V+10%
Frequency (Hz)	50/60
Rated input current (A)	23
No-load voltage (V)	65
Output current range (A)	40-200
Output voltage range (V)	20.8-26.4V
Duty cycle (%)	60% 170A
Efficiency (%)	85
Power factor	0.93
Insulation class	H
Case protect class	IP23
Dimension (L*W*H)(mm)	250X125X225
Weight (KG)	4



Main Technical Parameters :

	YADRIKA-400
Input voltage (V)	AC415V+10%
Frequency (Hz)	50/60
Rated input capacity (KVA)	17
Rated input current (A)	23.6
No-load voltage (V)	75
Duty cycle (%)	60% 400A 100% 310A
Output current range	20-400
Efficiency (%)	85
Insulation class	H
Case protect class	IP23
Dimension (L*W*H)(mm)	460X220X365
Weight (KG)	17
Suitable electrode rod	2.5/3.15/4.0



WITH REMOTE CONTROL